

Turbo 440 D



**Gianni
Ferrari**





GTM - GSM
15,5-16 hp



GTR
16-21 hp



GTS
22-23 hp



GT
28 hp



TURBO Z
22-40 hp



TURBOGRASS
22-23 hp



PG - SR
22-28 hp



TURBO 1-1W-2-4
28-50 hp



TURBOLOADER
22-44 hp

TECHNICAL FEATURES

► Modello	Turbo Z 440 D	
► Engine	Diesel Kubota V1505-T 40 hp / 1.498 cc. 4 / Liquid Pressure lubrication system with gear pump – cyclone-type air filter – fuel filter 43 L	
► Hydrostatic transmission	Pumps Danfoss variable displacement axial piston pumps Motors Danfoss axial piston motors on reduction gears Driving wheels 2WD Max forward speed 18 km/h Driving system Zero Turning Radius (ZTR) 2 control levers with Easy Control Panel (ECP™) Brakes Hydrostatic service brake (neutral position). Dual disc parking brake on transmission	
► Seat	Model Delux Grammer seat with lumbar support and headrest. Adjustable armrest and backrest Seat suspension Parallelogram suspension with 3 adjustable height position and driver's weight adjustment (50 kg to 130 kg)	
► Wheels/Tyres	Front Turf tyres 24 x 12.00 - 12 Front bar tread tyres (optional) 24 x 12.00 - 12 Oscillating rear axle 13 x 6.50 - 6	
► Power Take-Off	Type / Engagement Mechanical, with PTO shaft / Electric engagement by PTO button	
► Front lift	Type Hydraulic with 2 hydraulic rams	
► Electrical system	Battery 12 V / 70 Ah – battery isolator master switch as standard Safety sensors EEC European Standard / ISO Standard equipment Hour meter – coolant temperature Warning system Engine oil pressure – coolant temperature – battery (alternator fault) – glowplug – parking brake On-road use equipment As standard	
► Weight and measures (tractor unit only, basic version)	Unloaded weight 800 kg Length / Width / Height 247 x 142 x 132 (200)* cm	

*with ROPS folded down (upright)

The availability of models, versions and trim may vary depending on the country.

ATTACHMENTS

► 160 Dual-Cut™ mulching / rear discharge deck	Cutting width / No. Blades 155 cm (61") / 3 blades Cutting height adjustment Quick adjustment with SA™ lever, 2 cm to 8 cm Vertical position Hydraulic Weight 200 kg	
► Side discharge deck	Cutting width / No. Blades 150 cm (59") / 3 blades Cutting height adjustment Quick adjustment with SA™ lever, 2 cm to 8 cm Vertical position Hydraulic Weight 140 kg	
► Rear discharge deck	Cutting width / No. Blades 165 cm (65") / 4 blades Cutting height adjustment Quick adjustment with SA™ lever, 2 cm to 8 cm Vertical position Hydraulic Weight 190 kg	
► Flail mower	Cutting width / Blade reel 150 cm (59") / 100 flails (50 pairs) Cutting height adjustment 2 cm to 9 cm Weight 240 kg	
► Aerator / dethatcher	Working width / Blade reel 100 cm (40") / 28 mobile blades Weight 90 kg	
► Snow blade	Working width / Angling 175 cm (69") / ± 30°, hydraulic Weight 140 kg	

www.gianniferrari.com

In their constant bid to improve performance levels, Gianni Ferrari reserves the right to alter any technical aspects or performance, without prior warning. Likewise the models in this catalogue are subject to change. No liability is accepted for any possible misprints.

