

In addition to its use as applicator for approved plant protection chemicals, the new SOLO Master 466evolution is popular in vector control especially in subtropic and tropic regions. It is particularly well suited for that purpose in conjunction with the new ULV nozzle 49480 that produces very fine droplets.

The striking design of the mister fan housing integrates all functional components such as starter, fuel tank, spark plug, air filter and carburetor and provides the SOLO Master 466evolution with an unmistakable appearance.

The Master 466 evolution combines very high performance mistblower with low product weight. The air volume of 1400 m³/h produces efficient spray performance with excellent operator control and unsurpassed carrying comfort.

Sturdy construction

- Completely new, very robust frame
- High performance, low-emission 66.5cm3 SOLO 2-stroke engine to provide sufficient air power to penetrate dense plant foliage
- Aluminum crankcase and high value engine components

- New, high volume liquid tank with UV ray protection
- Robust blower housing made of high resistant plastic material

Significant, practical features

- Unsurpassed carrying comfort like a trekking backpack: ergonomically shaped and padded tank frame. Padded and wide shoulder straps in conjunction with large sized and padded hip belt
- Large, robust liquid tank
- Filler inlet 150 mm diameter
- Inlet filter made of stainless-steel mesh
- Raised edge on the underside of the liquid tank prevents inadvertently spilled liquids run-off to the operator's side
- Very sturdy frame with integrated carrying handle and stand
- Back part with service flap to access blower
- Large fuel tank to allow long work periods
- Ergonomically arranged single hand multifunction control for throttle, spray volume and start/stop
- Easy to start with incorporated fuel pump assistance

- Compact product measurements and very low product weight
- Effective vibration control

Modell BestNr. 46601 46603 (EU/US)	MASTER 466 evolution
Engine	SOLO 2-Stroke
Displacement	66.5 ccm
Power	2.1 kW (2.9 PS)
Fuel tank capacity	1,4 l
Tank capacity	141
Maximum fan air volume	1400 m³/h
Horizontal reach	11 m
Dry weight	10,0 kg (46601) / 10,1 (46603)
Carburator	Diaphragm with primer pump
Standard delivery	SOLO special misting nozzle with 4 settings, wide spray grille
Available acces- sories	ULV-nozzle Twin nozzle Extension tube Liquid booster pump